

CDV-43K



The Ultra Monitor is a 4.3" hand-set type product that includes all that is essential for a monitor. Users will find it to be highly efficient as the device has incorporated the most fundamental and essential functions with its

FINE COMMUNICATION

4.3" color monitor that applied vivid FINE VIEW technology and outstanding audio quality with handset.

INTERCOMMUNICATION

Up to 2 monitors and interphones each are expandable per household, providing intercommunication function.

DOOR ENTRY

It creates a safer and more convenient living environment with entrance front door release control function.

FUNCTION

- Support 2 monitors, 1 camera and 2 Interphones(CDV-43K)
- Support 2 monitors, 2 cameras and 2 Interphones(CDV-43K2)
- Intercommunication with sub monitor and interphone.
- Built-in memory storing in SD memory (SD Card is not included CDV-43KM)

SPECIFICATION

Power source	AC 100-240V, 50/60Hz	LCD size	4.3 inch wide color LCD
Mount type	Wall-mounted type	Operating temp.	0°C~40°C
Wiring	Door camera : 4 wires Interphone : 4 wires	Distance	Door camera : 50m(0.65Ø) Interphone : 30m(0.65Ø)
Consumption	Standby(CDV-43K, CDV-43K2) : 2.5W Standby(CDV-43KM) : 3.7W Operating : 8W	Dimension(mm)	157(W)x167(H)x28(D)

WIRING DIAGRAM

CDV-43K
CDV-43KM



CDV-43K2



DRC-40K



FUNCTION

- Illuminance sensor
- Wall-mounted type
- Built-in white LED
- Out door model
- House call and talk

SPECIFICATION

Power source	12V(From monitor)	Operating temp.	-10°C~50°C
Wiring	4 wires	Camera view angle	Horizontal 75°/ Vertical 55°
Distance	50m (Ø0.65)	Dimension(mm)	96(W)×155(H)×32(D)